

## MINIBAR COFOR

Description	Photo	Approval	Description	Photo	Approval
<p><b>Model: XC-25</b>  <b>Capacity: 25 Litre</b>  <b>Unit Size(WxDxH):</b> 350*385*460mm  <b>Carton Size(WxDxH):</b> 390*425*515mm  <b>Packing:</b> 1 pc/CTN  <b>N.W./G.W.:</b> 11.5/13KGS  <b>FCL:</b> 312PCS/20GP, 624PCS/40GP, 780PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:0-10°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>	<p><b>Model: XC-32</b>  <b>Capacity: 32 Litre</b>  <b>Unit Size(WxDxH):</b>400*405*530mm  <b>Carton Size(WxDxH):</b>440*460*595mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 14/16KGS  <b>FCL:</b>220PCS/20GP, 420PCS/40GP,500PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:0-10°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>
<p><b>Model: XC-25G</b>  <b>Capacity: 25 Litre</b>  <b>Unit Size(WxDxH):</b> 350*385*460mm  <b>Carton Size(WxDxH):</b> 390*425*515mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 11.5/13KGS  <b>FCL:</b> 312PCS/20GP, 624PCS/40GP, 780PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:6-12°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>	<p><b>Model: XC-32G</b>  <b>Capacity: 32 Litre</b>  <b>Unit Size(WxDxH):</b>400*405*530mm  <b>Carton Size(WxDxH):</b>440*460*595mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 14/16KGS  <b>FCL:</b>220PCS/20GP, 420PCS/40GP,500PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:6-12°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>
<p><b>Model: XC-28</b>  <b>Capacity: 28 Litre</b>  <b>Unit Size(WxDxH):</b> 400*365*480mm  <b>Carton Size(WxDxH):</b> 440*410*545mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 12.6/14.6KGS  <b>FCL:</b> 260PCS/20GP, 540PCS/40GP, 660PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:0-10°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>	<p><b>Model: XC-36</b>  <b>Capacity: 36 Litre</b>  <b>Unit Size(WxDxH):</b>435*430*465mm  <b>Carton Size(WxDxH):</b>475*475*525mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 15/17KGS  <b>FCL:</b> 200PCS/20GP, 420PCS/40GP, 520PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:0-10°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>
<p><b>Model: XC-28G</b>  <b>Capacity: 28 Litre</b>  <b>Unit Size(WxDxH):</b> 400*365*480mm  <b>Carton Size(WxDxH):</b> 440*410*545mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 12.6/14.6KGS  <b>FCL:</b> 260PCS/20GP, 540PCS/40GP, 660PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:6-12°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>	<p><b>Model: XC-36G</b>  <b>Capacity: 36 Litre</b>  <b>Unit Size(WxDxH):</b>435*430*465mm  <b>Carton Size(WxDxH):</b>475*475*525mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 15/17KGS  <b>FCL:</b> 200PCS/20GP, 420PCS/40GP, 520PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:6-12°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>
<p><b>Model: XC-30</b>  <b>Capacity: 30 Litre</b>  <b>Unit Size(WxDxH):</b> 400*405*480mm  <b>Carton Size(WxDxH):</b>440*460*545mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 13.5/15KGS  <b>FCL:</b> 240PCS/20GP, 480PCS/40GP, 570PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:0-10°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>	<p><b>Model: XC-38</b>  <b>Capacity: 40 Litre</b>  <b>Unit Size(WxDxH):</b>435*430*565mm  <b>Carton Size(WxDxH):</b>475*475*620mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 17/19KGS  <b>FCL:</b> 190PCS/20GP, 280PCS/40GP,450PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:0-10°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>
<p><b>Model: XC-30G</b>  <b>Capacity: 30 Litre</b>  <b>Unit Size(WxDxH):</b> 400*405*480mm  <b>Carton Size(WxDxH):</b>440*460*545mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 13.5/15KGS  <b>FCL:</b> 240PCS/20GP, 480PCS/40GP, 570PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:6-12°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>	<p><b>Model: XC-38G</b>  <b>Capacity: 40 Litre</b>  <b>Unit Size(WxDxH):</b>435*430*565mm  <b>Carton Size(WxDxH):</b>475*475*620mm  <b>Packing:</b>1 pc/CTN  <b>N.W./G.W.:</b> 17/19KGS  <b>FCL:</b> 190PCS/20GP, 280PCS/40GP,450PCS/40HQ</p> <p>*cooling by absorption system                      *power supply: 12V/50HZ,110V/60Hz, 220V-240V/50Hz                      *rated power: 60 W (AC110V/220V; DC24V/12V)                      *power consumption: 0.8-1.2kW-h/24h                      *refrigerant: R717/230g                      *climate classification: N                      *temperature:6-12°C                      *optional colors, foamed door, glass door, wooden door</p>		<p>CE                      ROHS                      CCC                      CB</p>